

# 899S

Stainless Steel Strainer



Via Circonvallazione, 10  
13018 Valduggia (VC), Italy  
Tel: +39 0163 47891  
Fax: +39 0163 47895  
www.vironline.com



Stainless steel strainer  
Threaded F/F (ISO 7/1 Rp)  
Stainless steel strainer (mesh 450µm)

PN40

For DN≤50: max 40bar up to 85°C, max 16bar above  
For DN≥65: max 40bar up to 85°C, max 10bar above  
Free of CE marking (cat. according to Art. 4.3 Dir. 2014/68/EU)

Working conditions

- Suitable for: water, -20°C to +180°C  
below 0°C only for water with added antifreeze fluids
- Not suitable for: gases group 1 & 2, liquids group 1 (Dir. 2014/68/EU)

## PARTLIST

N.	Part	Material	Norm
1	Body	Stainless steel	SS316
3	Strainer	Stainless steel	SS316
4	Gasket	PTFE	-
2	Bonnet	Stainless steel	SS316

## DIMENSIONS

DN	T	H [mm]	A [mm]	Weight [g]
015	1/2"	45	59	150
020	3/4"	60	73	260
025	1"	63	84	370
032	1 1/4"	80	97	530
040	1 1/2"	88	106	750
050	2"	109	127	1260
065	2 1/2"	138	165	2350
080	3"	153	188	3760
100	4"	196	232	6000

